

# ( HPD)

```
•   " " .      " " ,      hpd.conf( hydra user hydra password).
•   ,      " "
•   " " ( ),
```

*hpd.conf( hpd):*

```
# -
log path = /var/log/hpd/hpd.log
#
log level = debug
# -
log rotate size = 10240
# -
log rotate count = 25
# PID-
pid path = /var/run/hydra/hpd.pid

#
plugins directory = plugins
#
plugins list = osmp

# HTTP-
basic server status = off
# IP- HTTP-
basic server ip = 127.0.0.1
# HTTP-
basic server port = 9080
# HTTP-
basic server plugins list = osmp

# HTTPS-
ssl server status = on
# IP- HTTPS-
ssl server ip = 127.0.0.1
# HTTPS-
ssl server port = 9443
# PEM- HTTPS-
ssl server pem path = /etc/hpd/cert/ssl.pem
# HTTPS-
ssl server plugins list = osmp

# HTTPS-
cv-ssl server status = off
# IP- HTTPS-
cv-ssl server ip = 127.0.0.1
# HTTPS-
cv-ssl server port = 9444
# PEM- HTTPS-
cv-ssl server pem path = /etc/hpd/cert/ssl.pem
# HTTPS-
cv-ssl server plugins list = osmp

# TCP/IP-Socket-
socket server status = off
# IP- TCP/IP-Socket-
socket server ip = 127.0.0.1
# TCP/IP-Socket-
socket server port = 9000
# , TCP/IP-Socket-
socket server plugin = ncc
# TCP/IP-Socket-
socket server end message char code = 3
```

```
#  
tracking server status = off  
#  
tracking server plugins list = cyberpos  
# ,  
tracking server tracking interval = 300  
  
#  
database name = dev  
#  
database user = AIS_PAYMENTS  
#  
database password = read_manual  
  
#  
hydra user = hpd  
#  
hydra password = hydra_payment_daemon  
  
#  
internal error message = " "  
  
## ( )  
  
# ,  
# :  
# account -  
# user -  
# tel_no -  
# contract_doc_no -  
# bill_doc_no -  
payment field = account  
#  
allow company paying = 0  
# ,  
#users group =  
# Regexp,  
check regexp = ^\w+$  
#  
fee = 0  
# ISO-4217  
currency = RUB  
#  
pay type = RMM_KIND_PaySys  
#  
failed check message = " "  
#  
incorrect format message = " "  
#  
already charged transaction message = " "  
#  
failed pay message = " "  
  
## osmp (Qiwi)  
  
#  
osmp bank code =  
# ( )  
osmp to account =  
  
## wellpay  
  
# wellpay shop id = 738912  
# wellpay shop password = fb6b4c2a01  
  
## yamoney(.)  
# yamoney shop id = 738912
```

```
# yamoney shop password = fb6b4c2a01
#
# yamoney timezone offset = 0

#     ipriv ckecker
ipriv checker path = /opt/hpd/opt/ipriv/checker/checker
#     ipriv
ipriv config path = /etc/hpd/ipriv/checker.ini
```

( )

:

```
< > bank code = <     >
< > to account = <           >
```

```
plugins list() serverplugins list( ).
```

yamoney (.):

```
# .
yamoney bank code = .
yamoney to account =
yamoney shop id = 77777
yamoney shop password = secret
```

( )

hpd . . . :

```
< > base plugin = <   >
< > bank code = <     >
< > to account = <           >
```

```
plugins list() serverplugins list( ).
```

wellpay:

```
# 
plugins list = osmp, wellpay_sfera
...
#   HTTPS-
ssl server plugins list = osmp, wellpay_sfera
...
#   wellpay_sfera (wellpay)
wellpay_sfera base plugin = wellpay
wellpay_sfera bank code =
wellpay_sfera to account =
wellpay_sfera shop id = 777777
wellpay_sfera shop password = secret
```