

Cyberplat WebClient ()

1. hpd Latera.
2. - /etc/hpd/hpd.conf, SSL- *webclient*.
3. *webclient*:

```
webclient bank code = Terminal  
webclient to account = Terminal
```

- (bank code) (to account) (.).
4. /opt/hydra/hpd/opt/ipriv/lib *ipriv* :

```
hpd@bill:~/opt/ipriv/lib$ make && \  
make install
```

5. *checker* /opt/hpd/opt/ipriv/checker:

```
hpd@bill:~/opt/ipriv/checker$ make && \  
make install
```

1. WebClient.zip C:\WebClient.
2. C:\WebClient\config\config.xml <dealer_info> .
3. C:\WebClient\config\operators.xml:
 - a. config.xml <dealer_info> .
 - b. <url> <check> IP- , hpd. :192.168.0.1:9443.
 - c. <url> <payment> IP- , hpd. :192.168.0.1:9443.
 - d. <url> <status> IP- , hpd. :192.168.0.1:9443.
4. , C:\WebClient\keys /etc/hpd/ipriv/keys (keypath checker.ini).
5. WebClient.

1. /etc/hpd/ipriv/checker.ini:
 - a. keynumber = <serial_no> C:\WebClient\config\config.xml .
 - b. bankkey = <serial_no> C:\WebClient\config\config.xml .
 - c. password = <sec_password> C:\WebClient\config\config.xml .
2. hpd :/etc/init.d/hpd start