

(HPD)

- `"" . " ", hpd.conf(hydra user hydra password).`
- `, . "".`
- `"" (), .`

hpd.conf(**hpd**):

```
# -
log path = /var/log/hpd/hpd.log
#
log level = debug
# - ,
log rotate size = 10240
# -
log rotate count = 25
# PID-
pid path = /var/run/hydra/hpd.pid

#
plugins directory = plugins
#
plugins list = osmp

# HTTP-
basic server status = off
# IP- HTTP-
basic server ip = 127.0.0.1
# HTTP-
basic server port = 9080
# HTTP-
basic server plugins list = osmp

# HTTPS-
ssl server status = on
# IP- HTTPS-
ssl server ip = 127.0.0.1
# HTTPS-
ssl server port = 9443
# PEM- HTTPS-
ssl server pem path = /etc/hpd/cert/ssl.pem
# HTTPS-
ssl server plugins list = osmp

# HTTPS-
cv-ssl server status = off
# IP- HTTPS-
cv-ssl server ip = 127.0.0.1
# HTTPS-
cv-ssl server port = 9444
# PEM- HTTPS-
cv-ssl server pem path = /etc/hpd/cert/ssl.pem
# HTTPS-
cv-ssl server plugins list = osmp

# TCP/IP-Socket-
socket server status = off
# IP- TCP/IP-Socket-
socket server ip = 127.0.0.1
# TCP/IP-Socket-
socket server port = 9000
# , TCP/IP-Socket-
socket server plugin = ncc
# TCP/IP-Socket-
socket server end message char code = 3
```

```

#
tracking server status = off
#
tracking server plugins list = cyberpos
# ,
tracking server tracking interval = 300

#
database name = dev
#
database user = AIS_PAYMENTS
#
database password = read_manual

# ""
hydra user = hpd
# ""
hydra password = hydra_payment_daemon

#
internal error message = " "

## ( )

# ,
# :
# account -
# user -
# tel_no -
# contract_doc_no -
# bill_doc_no -
payment field = account
#
allow company paying = 0
# ,
#users group =
# Regexp,
check regexp = ^\w+$
#
fee = 0
# ISO-4217
currency = RUB
#
pay type = RMM_KIND_PaySys
#
failed check message = " "
#
incorrect format message = " "
#
already charged transaction message = " "
#
failed pay message = " "

## osmp (QIWI)

#
osmp bank code =
# ( )
osmp to account =

## wellpay

# wellpay shop id = 738912
# wellpay shop password = fb6b4c2a01

## yamoney (.)

# yamoney shop id = 738912

```

```
# yamoney shop password = fb6b4c2a01
# ,
# yamoney timezone offset = 0

# ipriv ckecker
ipriv checker path = /opt/hpd/opt/ipriv/checker/checker
# ipriv
ipriv config path = /etc/hpd/ipriv/checker.ini
```

()

:

```
< > bank code = < >
< > to account = < >
```

plugins list() server plugins list().

yamoney (.):

```
# .
yamoney bank code = .
yamoney to account = .
yamoney shop id = 77777
yamoney shop password = secret
```

()

hpd . :

```
< > base plugin = < >
< > bank code = < >
< > to account = < >
```

plugins list() server plugins list().

wellpay:

```
#
plugins list = osmp, wellpay_sfera
...
# HTTPS-
ssl server plugins list = osmp, wellpay_sfera
...
# wellpay_sfera (wellpay)
wellpay_sfera base plugin = wellpay
wellpay_sfera bank code =
wellpay_sfera to account =
wellpay_sfera shop id = 777777
wellpay_sfera shop password = secret
```